





STACE OFFICE | KIDS STUDIOS STUTT GART | SWITZERLAND



DINOR

High voltage
Ceiling suspended

1.0 LED

LED PCB 12W | 50-60Hz
phase cut trailing edge dim
aluminium
white cable on request

1.0 E27

G95 max. 15W | E27
100-240VAC | 50-60Hz
aluminium
white cable on request

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

CODE
W914110B0

BH | Semi recessed single base
ceiling base round | ø84

CODE
W914150B0

CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
IH | Wall base

more infos on page 253

IP20 L80|60K

1800-2850K | CRI >90 | 570lm

CODE
255188BG9
255188BB9



VOLTAGE
220-240VAC
110-130VAC

CODE
W2551E0BG0
W2551E0BB0

OPTIONAL

G95 10W | E27 | 110-130VAC
phase cut trailing edge dim | opal

CODE
2700K | 1060lm
W9087E893
more options and specs on page 465



DINOR

High voltage
Ceiling suspended



CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

CODE
W914110B0

BH | Semi recessed single base
ceiling base round | ø84

CODE
W914150B0

CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
IH | Wall base
more infos on page 253

IP20 L80/60K
1800-2850K | CRI >90 | 750lm

CODE
255288BG9
255288BB9

VOLTAGE
220-240VAC
110-130VAC

2.0 E27

G95 max. 15W | E27
100-240VAC | 50-60Hz
aluminium
white cable on request

IP20

CODE
W2552E0BG0
W2552E0BB0

OPTIONAL



G95 10W | E27 | 110-130VAC
phase cut trailing edge dim | opal
CODE
2700K | 1060lm W9087E893
more options and specs on page 465



PRIVATE RESIDENCE | INTERIOR DESIGN BY HUGAMA STUDIO HUNGARY



DINOR
High voltage
Ceiling suspended



3.0 LED

LED PCB 12W | 50-60Hz
phase cut trailing edge dim
aluminium
white cable on request

3.0 E27

G95 max. 15W | E27
100-240VAC | 50-60Hz
aluminium
white cable on request

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

CODE
W914110B0

BH | Semi recessed single base
ceiling base round | ø84

CODE
W914150B0

CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
IH | Wall base

more infos on page 253

IP20 L80/60K

1800-2850K | CRI >90 | 830lm

CODE
255388BG9
255388BB9

VOLTAGE
220-240VAC
110-130VAC

CODE
W ...
WL ...

IP20

CODE
W2553E0BG0
W2553E0BB0

OPTIONAL

G95 10W | E27 | 110-130VAC
phase cut trailing edge dim | opal

CODE
2700K | 1060lm
W9087E893
more options and specs on page 465